

LT 84 / LS 84 / SLT 42



Performance features

- » For controlling ventilation drives
- » Self-explanatory symbols
- » Versions for flush-mounted and surface-mounted installation and for moisture-prone areas

Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-U

63.701.29

Ventilation button

- » For controlling a ventilation group
- » Ventilation OPEN / STOP / CLOSED via double button with 2 unlocked normally open contacts
- » For installing in 55 mm flush-mounted socket (not included)

Input voltage	24 V DC
Type of protection	IP 20
Housing	Plastic
Colour	White
W x H	80 x 80 mm
Weight	0.15 kg



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-U-SD

63.701.35

Ventilation button

- » For controlling a ventilation group
- » Ventilation OPEN / STOP / CLOSED via double button with 2 unlocked normally open contacts
- » With integrated LED readout OPEN
- » For installing in 55 mm flush-mounted socket (not included)

Input voltage	24 V DC
Type of protection	IP 20
Housing	Plastic
Colour	White
W x H	80 x 80 mm
Weight	0.15 kg



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-U-V


63.701.30

Ventilation button


- » For controlling a 230 V AC ventilation group
- » Ventilation OPEN / STOP / CLOSED via double button; buttons mechanically interlocked; STOP by releasing the button
- » For installing in 55 mm flush-mounted socket (not included)

Input voltage	230 V AC
Type of protection	IP 20
Housing	Plastic
Colour	White
W x H	80 x 80 mm
Weight	0.30 kg




Type	Art. No.	Description	Technical data	
LS 84-U-V	63.701.45	Ventilation switch <ul style="list-style-type: none">» For controlling a 230 V AC ventilation group» Ventilation OPEN / STOP / CLOSED via double button; buttons mechanically interlocked; STOP by repeated/renewed press of rocker switch back to starting position» For installing in 55 mm flush-mounted socket (not included)	Input voltage	230 V AC
			Type of protection	IP 20
			Housing	Plastic
			Colour	White
			W x H	80 x 80 mm
			Weight	0.30 kg



Type	Art. No.	Description	Technical data	
LT 84-U-W	63.701.31	Ventilation switch <ul style="list-style-type: none">» Automatic switch for weather/temperature ON / OFF» For installing in 55 mm flush-mounted socket (not included)	Input voltage	24 V DC
			Type of protection	IP 20
			Housing	Plastic
			Colour	White
			W x H	80 x 80 mm
			Weight	0.30 kg




Type	Art. No.	Description	Technical data													
SLT 42-U	30.401.10	Key vent button <ul style="list-style-type: none">» For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels» Function: Ventilation OPEN / CLOSED via key operated changeover contact» For installing in deep 55 mm flush-mounted sockets (not included)» Profile semi-cylinder not included in scope of supply	<table><tr><td>Input voltage</td><td>24 V DC</td></tr><tr><td>Type of protection</td><td>IP 20</td></tr><tr><td>Housing</td><td>Plastic</td></tr><tr><td>Colour</td><td>White</td></tr><tr><td>W x H</td><td>80 x 80 mm</td></tr><tr><td>Weight</td><td>0.15 kg</td></tr></table>	Input voltage	24 V DC	Type of protection	IP 20	Housing	Plastic	Colour	White	W x H	80 x 80 mm	Weight	0.15 kg	
Input voltage	24 V DC															
Type of protection	IP 20															
Housing	Plastic															
Colour	White															
W x H	80 x 80 mm															
Weight	0.15 kg															





Type	Art. No.	Description	Technical data													
SLT 42-U-SD	30.400.50	Key vent button <ul style="list-style-type: none">» For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels» Function: Ventilation OPEN / CLOSED via key operated changeover contact» With integrated LED readout OPEN» For installing in deep 55 mm flush-mounted sockets (not included)» Profile semi-cylinder not included in scope of supply	<table><tr><td>Input voltage</td><td>24 V DC</td></tr><tr><td>Type of protection</td><td>IP 20</td></tr><tr><td>Housing</td><td>Plastic</td></tr><tr><td>Colour</td><td>White</td></tr><tr><td>W x H</td><td>80 x 80 mm</td></tr><tr><td>Weight</td><td>0.15 kg</td></tr></table>	Input voltage	24 V DC	Type of protection	IP 20	Housing	Plastic	Colour	White	W x H	80 x 80 mm	Weight	0.15 kg	
Input voltage	24 V DC															
Type of protection	IP 20															
Housing	Plastic															
Colour	White															
W x H	80 x 80 mm															
Weight	0.15 kg															





Type	Art. No.	Description	Technical data													
SLT 42-A	30.400.30	Key vent button <ul style="list-style-type: none">» For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels» Function: Ventilation OPEN / CLOSED via key operated changeover contact» Profile semi-cylinder not included in scope of supply	<table><tr><td>Input voltage</td><td>24 V DC</td></tr><tr><td>Type of protection</td><td>IP 54</td></tr><tr><td>Housing</td><td>Aluminium</td></tr><tr><td>Colour</td><td>Light grey</td></tr><tr><td>W x H x D (max.)</td><td>75 x 75 x 52 mm</td></tr><tr><td>Weight</td><td>0.45 kg</td></tr></table>	Input voltage	24 V DC	Type of protection	IP 54	Housing	Aluminium	Colour	Light grey	W x H x D (max.)	75 x 75 x 52 mm	Weight	0.45 kg	
Input voltage	24 V DC															
Type of protection	IP 54															
Housing	Aluminium															
Colour	Light grey															
W x H x D (max.)	75 x 75 x 52 mm															
Weight	0.45 kg															



Type	Art. No.	Description	Technical data													
SLT 42-A-SD	30.400.40	Key vent button <ul style="list-style-type: none">» For manually opening and closing a ventilation group in conjunction with D+H SHEV or ventilation control panels» Function: Ventilation OPEN / CLOSED via key operated changeover contact» With integrated LED readout OPEN» Profile semi-cylinder not included in scope of supply	<table><tr><td>Input voltage</td><td>24 V DC</td></tr><tr><td>Type of protection</td><td>IP 54</td></tr><tr><td>Housing</td><td>Aluminium</td></tr><tr><td>Colour</td><td>Light grey</td></tr><tr><td>W x H x D</td><td>75 x 75 x 52 mm</td></tr><tr><td>Weight</td><td>0.45 kg</td></tr></table>	Input voltage	24 V DC	Type of protection	IP 54	Housing	Aluminium	Colour	Light grey	W x H x D	75 x 75 x 52 mm	Weight	0.45 kg	
Input voltage	24 V DC															
Type of protection	IP 54															
Housing	Aluminium															
Colour	Light grey															
W x H x D	75 x 75 x 52 mm															
Weight	0.45 kg															



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

LT 84-A

63.701.36

Ventilation button

- » For controlling a ventilation group
- » Suitable for surface-mounted installation in moisture-prone areas
- » Ventilation OPEN / STOP / CLOSED via double button with 2 unlocked normally open contacts

Input voltage	24 V DC
Type of protection	IP 44
Housing	Plastic
Colour	Light grey
W x H x D	70 x 70 x 45 mm
Weight	0.20 kg



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

AP-LT

63.701.33

Surface-mounted housing, single

- » For holding one SLT, LT or LS for surface-mounted installation

Housing	Plastic
Colour	White
W x H x D	80 x 80 x 35 mm
Weight	0.10 kg



Type	Art. No.	Description	Technical data
------	----------	-------------	----------------

PHZ 28

70.600.53

Profile semi-cylinder

- » For key vent button (SLT)
- » Including 3 keys

Weight	0.15 kg
--------	---------

