
CPS-B1-2.5-0101-FR



Performance features


- Compact SHEV control panel, specifically for stairwells
- Up to 2.5 A total drive current
- Stabilised output voltage
- Switchable SHEV safety functions: Fault equal to alarm, SHEV retriggering function and smoke detector remote reset
- Integrated comfort functions for daily ventilation
- Optional connection to rain detectors or wind / rain sensors without an additional module
- Connection of up to 2 SHEV operation panels per control panel
- Min. 72 hr battery backup supply

Accessories

Batteries	SHEV operation panel	Sensor systems
		

We reserve the right to make changes.
©2022 D+H Mechatronic AG, Ammersbek

Example of application



Technical data

	CPS-B1-2.5-0101-FR
Supply	230 V AC / 50 Hz / 140 VA
Stand-by power	< 2 W / 10 VA
Output	24 V DC / 2.5 A
Mode of operation monitoring	Continuous duty
Mode of operation Alarm / Ventilation	Short-time duty 30 % duty cycle
Type of protection	IP 32D
Temperature range	-5 °C … +40 °C
Line / Group	1 / 1
Housing	Plastic
Colour	White (~ RAL 9016)
Battery type	Typ 2 (2x)

Batteries must be ordered separately.

Approvals / Certificates

Find out about permission details from your D+H Partner.

Design

Type	Art. No.	W x H x D	Weight
CPS-B1-2.5-0101-FR	30.119.30	310 x 310 x 104 mm	1.87 kg